

Pre-Coat Acrylic Primer



Pre-Coat Acrylic Primer

DESCRIPTION:

- 100 percent acrylic-based primer
- Reduces the chance of efflorescence which may result from the cement content of various bases
- Enhances the appearance and uniformity of the finish
- Improves water resistance of Surewall EIF Systems
- Water-vapor permeable. Does not create a vapor retarder
- Improves finish coverage

USES:

Exterior and Interior:

- Required for:
Interior drywall
- Optional for:
Cementitious Base Coats:
for swirl textures finishes
Full Synthetic Base Coat:
for dark color finishes
Any surface suitable for Surewall finishes
Portland cement-based stucco

COMPOSITION:

- Binder base: 100 percent acrylic
- Water-based: VOC compliant
- Pigment base: Titanium dioxide
- Color: White or tinted to the color of Surewall finish

COVERAGE:

Depending on the condition of the substrate and method of application, approximate coverage is:

One coat: 1600-2000 sq. ft.
(150 - 185 m²)/pail

CONTAINER:

60 lb (27.7 kg) net weight in plastic pails.

- Storage: Protect from sun and freezing at all times.
 - Do not stack pails more than 3 pails high
- Shelf Life: One year if protected from sun and freezing.

DRYING TIME:

Approximately 1/2 to 4 hours depending on temperature, humidity, and substrate.

CLEANUP:

Water soluble prior to drying. Clean tools and containers with water prior to drying.

SURFACE PREPARATION:

- Remove surface contaminants such as dust or dirt without damaging the substrate.
- For previously painted surfaces, all loose and chalking paint must be removed, and glossy surfaces dulled.
- New concrete and masonry must be clean and cured a minimum of 28 days.
- Check concrete surfaces for alkalinity and treat. Any form-release agents or bond breakers must be removed.
- Uneven concrete or masonry can be leveled with either Flex or Prime-A-Flex Base Coat or other suitable, compatible product.
- For interior drywall, prepare as for painting.
- For additional options, contact Surewall Technical Services Department.

MIXING:

- Mix thoroughly. Up to 2 gallons (7.5L) of clean portable water can be added.

APPLICATION:

- Read the entire label before using this product.
- Apply with a roller, brush or suitable spray equipment in a continuous coat.
- Surewall Pre-Coat Acrylic Primer must be completely dry before any Surewall finish coating is applied.
- When using Surewall swirl texture finishes, the primer should be tinted to the color of the finish coating.
- Keep container closed when not in use.

LIMITATIONS:

- Ambient and surface temperatures must be 40°F (4°C) or higher during application and drying time. Provide supplemental heat and protection from precipitation as needed.
- Use only on surfaces that are sound, clean, dry, and free from any residue which may affect the ability of Surewall Pre-Coat Acrylic Primer to bond to the surface.
- Avoid application in direct sunlight in hot weather.

SUREWALL®

Corporate Office
ParexLaHabra, Inc.
4125 E. La Palma Avenue, Suite 250
Anaheim, CA 92807
(714) 778-2266
(866) 516-0061, Tech Line

Sales Office
Surewall
1870 Stone Mountain-Lithonia Road
Redan, GA 30074
(800) 537-2739

Plants
Redan, GA
Wilkes Barre, PA

